

PRODUCT : SAFING HARNESS

REF. NO. : SAFING 3

DOC. NO.	QI PRO/05
TYPE	PI
REVISION	01
DATE	01-11-2013

CONFORMING TO EN 362:2002,
EN 124:2002 & EN 813:2008



S	PHYSICAL PARAMETERS	GENERAL	ATTACHMENT ELEMENTS	<ul style="list-style-type: none"> One lateral attachment D-ring for full arrest. One front attachment D-ring at chest (lateral) for full arrest. One front (central) D-ring at waist level for Rope Access. Two lateral D-Rings at waist for Work Positioning.
			ADJUSTABILITY	<ul style="list-style-type: none"> Fully Adjustable shoulder, thigh straps & waist strap.
			CONVENIENCE	<ul style="list-style-type: none"> Shoulder straps & thigh straps are provided with automatic buckles & waist strap has combination buckles for easy adjustment, two tool holder loops & an extra large handle at the back for keeping extra karabiners and accessories. Lanyard keepers on shoulder straps have been provided for easy placement of two lanyards.
			ERGONOMICS	<ul style="list-style-type: none"> Heavily padded ventilated straps for extended comfort. Specially cushioned Shoulder, waist and thigh pads has been used for better shock absorption & comfort of the user. Equipped with lightweight aluminum D-Ring to