



**PRODUCT : RETRACTABLE BLOCK POLYMER CASING WITH G.J WIRE ROPE**

**REF. NO. : PFG006**

DOC. NO.	DP/WG/OS
ISSUE	01
REVISION	00
DATE	15-06-2016

**CONFORMING TO EN 360:2002**



<b>1</b>	<b>PHYSICAL PARAMETERS</b>	GENERAL		<ul style="list-style-type: none"> <li>Robust and Durable Plastic Casing.</li> <li>Swivel eye at the anchorage end.</li> <li>Swivel Steel Snap hook PN 162 with load indicator at attachment end.</li> <li>Galvanized steel wire rope (option of Nealing 5.5 wire rope available).</li> </ul>
		WEIGHT		2.07 kg
<b>2</b>	<b>METALLIC ASSEMBLY</b>	CABLE	MATERIAL BREAKING STRENGTH LENGTH	Galvanized steel wire rope Ø 4.5 mm 15 kN or 1530 kgf (Min.) 5 meter
		SWIVEL STEEL SNAP HOOK PN 162	MATERIAL FINISH	Alloy steel Galvanized with golden yellow/ silver passivation
		BREAKING STRENGTH		25 kN (min.)
<b>3</b>	<b>VITAL TEST COMPLIANCE</b>	STATIC STRENGTH	12 kN sustained for 3 minutes without any failure	
		DYNAMIC PERFORMANCE	100 kg mass free fall of 600 mm with the breaking force $\leq 6$ kN & arrest distance $\leq 2$ m	

